



POWERED

BESTFLEX®

POWERED 1.5 ROLLER CONVEYOR

FEATURES

WIDTH: 18", 24", or 30"

Determined by package size,
available conveying area and
application specific needs

LENGTH EXTENDED: 12' and up

Calculate total length needed,
including curvatures/obstructions

AXLE CENTER: 5", 4" or 3"

Package size determines necessary
axle center length (fully extended)

ROLLER TYPE: 1.5"Ø steel roller

Determined by package weight,
durability, operational flow control,
and application specific needs

DESCRIPTION

Flexible powered conveyors provide maximum productivity in shipping, transportation and packaging applications where usability and adaptability are needed.

With its innovative design, the **BestFlex® 1.5** powered roller conveyor requires less storage space when fully retracted and can service multiple docking doors for maximum productivity. By powering the conveyor, any package size can be moved any distance at variable rates of speed. It is an all power conveyor that has a capacity of 100 pounds per linear foot.

The **BestFlex 1.5** model features an easy and quick way to change out the drive belts giving you added durability and less maintenance down time.



BESTFLEX®

POWERED 1.5 ROLLER CONVEYOR



SPECIFICATIONS

| 18" WIDTHS | | 24" WIDTHS | | 30" WIDTHS | | LENGTH ADJUSTMENT | |
|------------|----------|------------|----------|------------|----------|-------------------|------------|
| MODEL # | LEG SETS | MODEL # | LEG SETS | MODEL # | LEG SETS | EXTENDED | CONTRACTED |
| BFP1.51812 | 5 | BFP1.52412 | 5 | BFP1.53012 | 5 | 12' | 4' |
| BFP1.51824 | 8 | BFP1.52424 | 8 | BFP1.53024 | 8 | 24' | 8' |
| BFP1.51836 | 11 | BFP1.52436 | 11 | BFP1.53036 | 11 | 36' | 11' |
| BFP1.51848 | 14 | BFP1.52448 | 14 | BFP1.53048 | 14 | 48' | 14' |

All conveyor products can be modified to suit specific design requirements.

Please contact our sales representatives for details on sizes or options that are not listed. Lengths based on standard 5" axle centers.

STANDARD FEATURES

- Load capacity 100 lbs/ft
- Heavy duty 16 gauge precision bearing 1.5" Ø steel rollers
- 5" axle centers
- 31½" – 41½" adjustable conveyor heights
- Heavy duty steel square tubing powder coated black legs
- 6" x 2" heavy duty casters with brakes
- 1.59" aluminum extruded side plates with bolted construction
- Self-tracking design
- Durable DC drive motors with 120V A/C
- On/Off switches on both ends of conveyor
- Handles on each end of the unit

OPTIONS

- 4" and 3" axle centers
- Electronic photo eye package stop
- Zero pressure accumulation
- Indexing
- Leg connect brackets
- Electrical interface kit (allows multiple sections to operate together)

ACCESSORIES

- Herringbone transition
- Guide Track
- PowerTrax

TECHNICAL DATA

LEGS

Powder coated, heavy duty leg supports
1¼" square tubing welded cross brace

SIDE LINKS

1.59" aluminum alloy side links
Bolted construction

WARRANTY

Electrical: 12 month warranty
Mechanical: 24 month warranty

SERVICES AVAILABLE

Technical Support
Installation and Service
Maintenance
Application Support
Hardware Support